

PERFORMANCE FIRE RETARDANT FOAM ANECHOIC WEDGES

Sound Absorbing & Noise Blocking Products



PFRF - FIRE RETARDANT FOAM

| | |
|--|---|
| Size: | 24" x 48" and 48" x 48" |
| Thickness: | 1", 1.5", 2", 3", 4" |
| Density: | 2 lb / cubic foot |
| Flammability: | Class One |
| Flame Spread: | 10* |
| Smoke Density: | 50* |
| Colors: | Natural White Paint and Hypalon Color available |
| <ul style="list-style-type: none"> ▶ Welding Areas ▶ Churches & Schools ▶ Generator Plants ▶ High Temperatures | |

| Frequency (Hz) | 125 | 250 | 500 | 1K | 2K | 4K | NRC |
|----------------|-----|------|------|------|------|------|------|
| 2" PFRF-AW | .03 | .31 | .81 | 1.02 | 1.01 | .96 | .80 |
| 3" PFRF-AW | .13 | .74 | 1.26 | 1.18 | 1.12 | 1.03 | 1.10 |
| 4" PFRF-AW | .33 | 1.12 | 1.32 | 1.39 | 1.19 | 1.12 | 1.26 |

WEST COAST
SOUND SOLUTIONS

98 12TH STREET
SAN FRANCISCO, CA 94103
000111* / 1. PH
415 / 864 / 4447 FX
WWW.WESTCOASTSOUNDSOLUTIONS.COM

Call now to order your sound absorbing
products. **(888) 927- 7496**