



## Privacy Double Deflection Hangars (HND)

### FEATURES:

- ▶ Easily works with 3/16" Threaded Rod
- ▶ Embedded steel plates for uniform loading
- ▶ Oil + water resistant element
- ▶ High deflection, low natural frequency
- ▶ Can be used to support metal channel, then a drywall ceiling is attached to the metal channel.

### NOTE:

Do not exceed maximum load by more than 5%

MODEL	MAX LOAD (lbs)	DEFLECTION (inches)	Isolators Dimension (inches)				
			A		C	D	E
HND-A-1	30	2/5	3	1 3/8	2	2 1/4	3/8
HND-A-2	40	2/5	3	1 3/8	2	2 1/4	3/8
HND-A-3	70	2/5	3	1 3/8	2	2 1/4	3/8
HND-A-4	115	2/5	3	1 3/8	2	2 1/4	3/8
HND-B-1	165	1/2	4 1/2	1 7/8	2 1/4	3	1/2
HND-B-2	235	1/2	4 1/2	1 7/8	2 1/4	3	1/2
HND-B-3	375	1/2	4 1/2	1 7/8	2 1/4	3	1/2
HND-B-4	545	1/2	4 1/2	1 7/8	2 1/4	3	1/2

MODEL	Price
HND-A	Call now for pricing
HND-B	Call now for pricing

