SILENSEAL ACOUSTICAL SEALANT

UL CLASSIFIED & VOC COMPLIANT
NON-FLAMMABLE FORMULATION
WILL NOT HARDEN, CRACK OR SEPARATE



Benefits:

- Easy application / soap and water cleanup
- Non-staining and non-migrating
- Freeze thaw stable
- High degree of adhesive and cohesive strength
- Adheres to wood, concrete, glass, gypsum, metal and plastic
- More flexible than any other water based sealant





98 12TH STREET SAN FRANCISCO, CA 94103 PHONE: (888) 927-7496 FAX: (415) 864-4447 WWW.WESTCOASTSOUNDSOLUTIONS.COM



Silenseal Acoustical Sealant

Silenseal Acoustical Sealant is a one-part nonflammable product designed specially for the reduction of sound transmission in all types of wall partition systems. Its primary function is to achieve and maintain the specific Sound Transmission Class (STC) value of the system designed. Use to seal edges and seams of drywall and subfloor to prevent loss of sound isolation caused by leaks.

SPECIFICATIONS

Appearance	Brown Creamy Paste
Tube Size	29 oz.
Solids	67-70% by weight
Viscosity980,000 d	cps +/- 10% # spindle 1rpm
PH	7 -7.5
Flammability	Non-Flammable
VOC Content	<5 gr/liter (calculated)
Cure Time	2-7 days
Application temperature	40°F min
Storage	40 to 100 deg F
Clean Up	Soap and Water
Shelf Life	1 year

1/2" bead	22 linear ft.
3/8" bead	40 linear ft.
1/4" bead	89 linear ft.

Solve your noise problem. Call now to get it right the first time. (888) 927-7496

So you need expert design, product selection and installation instruction? We have the experience you need for a partnership that will work.