

SONEX CLASSIC PANELS

Sound Absorbing and Noise Blocking



FAMOUS ANECHOIC WEDGE SHAPE

PANEL SIZE OF 24" X 48", 2" THICK

AVAILABLE WITH SPECIAL COLORTEC PROCESS

PHYSICAL DATA

Material	Open-cell melamine-based foam
Density	0.5 to 0.7 lbs./cu. ft. (ASTM D3574-77)
Long-Term Service Temperature	302°F
Fire Resistance	Class 1 per ASTM E 84 (all finishes) Meets UL 1715 (willtec natural and colortec)
Flame Spread per ASTM E 84	Natural: 5, Painted: 10, Colortec: 10
Smoke Density per ASTM E 84	Natural: 50, Painted: 10, Colortec: 10
Microbial Growth	Passes UL 181, section 11
Fungus Resistance Rating	0 per ASTM G21
Finishes	Natural (white & light grey), Painted, Colortec or Colortec premium



Performance fire retardant foam

SOUND ABSORPTION

Finish	Thickness	Coefficients per ASTM C423-90a						NRC	Mounting
		125Hz	250Hz	500Hz	1kHz	2kHz	4kHz		
Natural (white and grey)	2"	0.05	0.31	0.81	1.01	0.99	0.95	0.80	A
Painted	2"	0.17	0.33	0.85	1.03	1.08	1.06	0.80	B
colortec (charcoal)	2"	0.05	0.31	0.81	0.96	0.97	0.97	0.75	A
colortec premium (charcoal)	2"	0.05	0.31	0.81	0.96	0.97	0.97	0.75	A

**Solve your noise problem. Call now
to get it right the first time (888) 927-7496**

Do you need expert design, product selection and installation instruction? West Coast Sound Solutions has the experience you need for a partnership that will work. Call Now (888) 927-7496



WEST COAST
SOUND SOLUTIONS

98 12TH STREET
SAN FRANCISCO, CA 94103
888 / 927 / 7496 PH
415 / 864 / 4447 FX

WWW.WESTCOASTSOUNDSOLUTIONS.COM

www.westcoastsoundsolutions.com