

# SONEX MINI PANELS

Sound Absorbing and Noise Blocking



SMALLER CONVOLUTED SURFACE PATTERN

IDEAL FOR MACHINE ENCLOSURES AND  
APPLICATIONS REQUIRING THINNER PANELS

PANEL SIZE OF 24" X 48" BY 1" OR 1 1/2"

SONEX Mini Panels provide excellent sound absorption, especially in environments requiring high-frequency noise control. Made with exclusive willtec® foam, SONEX Mini Panels are a safety-minded choice for use in machine enclosures and other confined spaces. willtec foam is Class 1 fire-rated according to ASTM E 84 for flame spread and smoke density. It can withstand constant temperatures above 300° Fahrenheit, and will char, but not ignite, at temperatures above 1100° Fahrenheit. willtec natural meets the corner burn test UL1715.

SONEX Mini Panels, available in natural or painted willtec, are easy to install on any wall and/or enclosure surface with pinta's acouSTIC water-based adhesive.

## PHYSICAL DATA

Material	Open-cell melamine-based foam
Density	0.5 to 0.7 lbs./cu. ft. (ASTM D3574-77)
Long-Term Service Temperature	302°F
Fire Resistance	Class 1 per ASTM E 84 (all finishes) Meets UL 1715 (willtec natural)
Flame Spread per ASTM E 84	Natural: 5, Painted: 10
Smoke Density per ASTM E 84	Natural: 50, Painted: 10
Microbial Growth	Passes UL 181, section 11
Fungus Resistance Rating	0 per ASTM G21
Finishes	Natural (white and light grey) or painted

## SOUND ABSORPTION

Finish	Thickness	Coefficients per ASTM C423-90a						NRC	Mounting
		125Hz	250Hz	500Hz	1kHz	2kHz	4kHz		
Natural (white and light grey)	1"	0.11	0.17	0.40	0.72	0.79	0.91	0.50	A
	1 1/2"	0.14	0.21	0.61	0.80	0.89	0.92	0.65	A

**Solve your noise problem. Call now  
to get it right the first time 888-666-5090**

Do you need expert design, product selection and installation instruction? Sound Isolation Company has the experience you need for a partnership that will work. Call Now 888-666-5090

98 12TH STREET  
SAN FRANCISCO, CA 94103  
888 / 927 / 7496 PH  
415 / 864 / 4447 FX

WWW.WESTCOASTSOUNDSOLUTIONS.COM