


RSIC-SI-WHI





RSIC-SI-WHI 5 LBS TO 80 LBS

**SHIPPED FULLY
ASSEMBLED
AND CALIBRATED**

PAC International, Inc. Tel: (866) 774-2100 Technical: (866) 649-2710 Web Site: www.pac-intl.com

PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710
RSIC® is a registered Trade Mark of PAC International, LLC.

RSIC-SI-WHI SOUND ISOLATION CLIP



80 Lb
40 Lb
30 Lb
20 Lb
10 Lb
5 Lb

Drywall Furring Channel:

- Furring Channel: Min 25 gauge hemmed edge, or 20 gauge standard. Meets or exceeds SSMA requirements
- Depth: 7/8"
- Width Bottom: 2-1/2" wide minimum.
- Width Top: 1-1/4" wide
- Splice drywall furring channel (hat track) with 6" overlap in mid span (between two clips) secure with 18 ga tie wire, or two 7/16" framing screws.

Carrier Channel Options:

- **48" spacing 16 gauge cold rolled channel (CRC)** dim: 1/2" x 1.5" x 1/2" SSMA cod : 150U050-54
- CRC and steel studs must meet or exceed SSMA standards
- Drywall Grid Follow manufacturer installation requirements

Fasteners:

- **RSIC-SI-WHI to Wood:** #8 x 1-5/8 inch minimum size coarse thread screw. (Recommended #12 or #10 x 1-5/8 inch hex head)
- **RSIC-SI-WHI to Steel:** # 8 x 1inch minimum size fine thread screw. (Recommended #12 or #10 x 1inch hex head)
- Hanger wire per manufacturer recommendations for load at each position.
- RSIC-SI-WHI clip is direct attached to the side of the framing members with screws

RSIC-SI-WHI Spring Isolator

- **Maximum Spacing:** 48" oc. With Cold Rolled Channel
- **Finish elevation is 1/2" below preset height.**
- Silver = 80 Lbs
- Red = 40 Lbs
- Green = 30 Lbs
- Blue = 20 Lbs
- White = 10 Lbs
- Yellow = 5 Lbs

PAC International, Inc. Tel: (866) 774-2100 Technical: (866) 649-2710 Web Site: www.pac-intl.com

PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710

RSIC® is a registered Trade Mark of PAC International, LLC.

RSIC-SI-WHI SOUND ISOLATION CLIP



Ceilings: RSIC-SI-WHI clips installed 48" oc

- Resilient Sound Isolation Clips (RSIC-SI-WHI) shall be max 48 inches on center .
- Any additional or non standard room dimensions need to be addressed by a professional engineer.
- Carefully remove RSIC-SI-WHI pre-assembled, and pre-calibrated clips from packaging.
- Be cautious to not rotate the RSIC-SI-WHI spring clips separate from the bracket. This may change the factory calibration of RSIC-SI-WHI.
- Verify the correct quantity of each RSIC-SI-WHI isolator (weight / color) is included in the shipment.
- Layout the RSIC-SI-WHI clips out on the floor (reflecting the ceiling above) Ensure there are no additional items required to complete the installation, IE: Additional blocking to support the RSIC-SI-WHI clips, or additional clips to support the drywall.
- Fasten the Resilient Sound Isolation Clip (RSIC-SI-WHI) to the side of the joist allowing for 1/2" deflection after the gypsum board has been installed.
- At the perimeter, the distance between the wall and first support for the drywall shall be less than 8"
- Tie hanger wire to the bottom loop of the RSIC-SI-WHI isolator clip.
- Tie the 16 Ga cold rolled channel or drywall grid to the hanger wire hung from the RSIC-SI-WHI clip.
- Follow Steel framing guidelines for spacing with CRC channel, and manufacturer installation guide for Drywall Grid systems.
- Install perimeter tape on wall at ¼ above finished ceiling height.
- Install gypsum board
- Caulk gap between gypsum board and wall.

- Silver 80 Lb field clips
- Red 40 Lb field and perimeter clips
- Green 30 Lb field and perimeter clips
- Blue 20 Lb field, perimeter and edge clips
- White 10 Lb edge, corner, and or infill clips
- Yellow 5 edge or corner clips

PAC International, Inc. Tel: (866) 774-2100 Technical: (866) 649-2710 Web Site: www.pac-intl.com

PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710
RSIC® is a registered Trade Mark of PAC International, LLC.

RSIC-SI-WHI SOUND ISOLATION CLIP



Calibration and Adjustment:

- The Pre-Calibration of the RSIC-SI-WHI clip is designed to deflect only 1/2" from its pre-loaded (pre-set) position when the full load has been applied.

Ceilings:

- Optional: Recommended add strong back consisting of 1.5" Cold Rolled Channel or drywall furring channel, on the top side of the standard drywall furring channel to assist in leveling the ceiling at or near the perimeter. The strong back shall be placed perpendicular to the main drywall furring channels
- Install the gypsum board to the drywall furring channel leaving a 1/8" to 1/4" gap around the perimeter of the entire ceiling.
- Caulk around the entire perimeter of the ceiling wall intersection.
- Use fire and smoke rated acoustical sealant where required.
- The RSIC-1 SI is engineered for use with a minimum of 2 layers of 5/8" gypsum board.

General Information:

- Resilient Sound Isolation Clip Spring Isolator (RSIC-SI-WHI), furring channel (hat track) and gypsum board shall not carry heavy loads such as Projectors, HVAC Ducting, Curtains, etc. For these items use additional RSIC isolation clips specifically designed for that purpose.
- Splice furring channel (hat track) with 6 inch overlap in mid span, secure with 18 ga. tie wire or with two framing screws (7/16")
- Seal all potential air leaks with non-hardening acoustical caulking to achieve best noise control results. Use fire rated sealant where required.
- When attaching the RSIC-SI-WHI clips to a steel Joist the minimum allowable thickness is 20 ga. (0.030).

Fire Test Information:

WWW.PAC-INTL.COM

Check UL Fire Resistance Directory File # R16638

Check UL's web pages. www.ul.com/database

Contact UL (877) UL-HELPS


PAC International, Inc. Tel: (866) 774-2100 Technical: (866) 649-2710 Web Site: www.pac-intl.com

PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710

RSIC® is a registered Trade Mark of PAC International, LLC.

RSIC-SI-WHI SOUND ISOLATION CLIP


Sample layout 48" oc.



PAC International, Inc. Tel: (866) 774-2100 Technical: (866) 649-2710 Web Site: www.pac-intl.com

PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710
RSIC® is a registered Trade Mark of PAC International, LLC.

RSIC-SI-WHI SOUND ISOLATION CLIP



Members of the International Code Council

WARRANTY DISCLAIMER AND LIABILITY LIMITATION LANGUAGE

NO EXPRESS OR IMPLIED WARRANTIES

THERE IS NO WARRANTY, REPRESENTATION OR CONDITION OF ANY KIND; AND ANY WARRANTY, EXPRESS OR IMPLIED, IS EXCLUDED AND DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow limitations on implied warranties, so the above limitation may not apply to you.

LIABILITY LIMITED TO RETURN OF PURCHASE PRICE

IT IS AGREED THAT SELLER'S LIABILITY AND PURCHASER'S SOLE REMEDY, WHETHER IN CONTRACT, UNDER ANY WARRANTY, IN TORT (INCLUDING NEGLIGENCE), IN STRICT LIABILITY OR OTHERWISE, SHALL NOT EXCEED THE RETURN OF THE AMOUNT OF THE PURCHASE PRICE PAID BY PURCHASER, AND UNDER NO CIRCUMSTANCES SHALL SELLER BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING, BUT NOT LIMITED TO, PERSONAL INJURY, PROPERTY DAMAGE, DAMAGE TO OR LOSS OF EQUIPMENT, LOST PROFITS OR REVENUE, COSTS OF RENTING REPLACEMENTS AND OTHER ADDITIONAL EXPENSES, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE PRICE STATED FOR THE EQUIPMENT IS A CONSIDERATION IN LIMITING SELLER'S LIABILITY AND PURCHASER'S REMEDY. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

SELLER NOT LIABLE FOR PURCHASER'S NEGLIGENCE

SELLER WILL NOT BE LIABLE FOR ANY DAMAGES, LOSSES OR EXPENSES AS A RESULT OF PURCHASER'S NEGLIGENCE, WHETHER DEEMED ACTIVE OR PASSIVE AND WHETHER OR NOT ANY SUCH NEGLIGENCE IS THE SOLE CAUSE OF ANY SUCH DAMAGE, LOSS OR EXPENSE.

MODEL FOR DEMONSTRATION PURPOSES ONLY

THE MODEL OR SAMPLE SHOWN BY SELLER TO BUYER IS USED FOR DEMONSTRATION PURPOSES ONLY. THERE IS NO WARRANTY THAT THE GOODS AS DELIVERED SHALL CONFORM TO THE MODEL OR SAMPLE, AND CONFORMITY OF THE GOODS TO THE MODEL OR SAMPLE IS NOT PART OF THE BASIS OF THE BARGAIN BETWEEN SELLER AND BUYER.

NO WARRANTY OR COMPLIANCE WITH SAFETY CODE OR REGULATION

SELLER DOES NOT WARRANT THAT ANY OF THE GOODS SOLD WILL MEET OR COMPLY WITH THE REQUIREMENTS OF ANY SAFETY CODE, BUILDING OR DWELLING CODE, OR REGULATION OF ANY STATE, MUNICIPALITY OR OTHER JURISDICTION.

NEVADA LAW APPLIES

SELLER AND BUYER AGREE THAT ALL ASPECTS OF THIS TRANSACTION INCLUDING THE APPLICABLE STATUTE OF LIMITATIONS SHALL BE GOVERNED BY THE INTERNAL LAW OF THE STATE OF NEVADA, AND NOT THE LAWS OF CONFLICTS.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

PAC International, Inc. Tel: (866) 774-2100 Technical: (866) 649-2710 Web Site: www.pac-intl.com

PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710
RSIC® is a registered Trade Mark of PAC International, LLC.