





Wall and Partition Facings and Accessories

See General Information for Wall and Partition Facings and Accessories

Type Soundproof Barrier (1 lb/sq ft.) membrane for optional use on one side of wall designs of the U300, U400, and V400 series. Also for optional use in floor-ceiling constructions of the L500 series over the subfloor.

For U300, U400 and V400 series designs, one layer of barrier applied to one side of wood or steel studs between stud and gypsum board per manufacturer\'s recommendations. When installed, the Soundproof Barrier flex at midspan between the studs shall be max. 1 in. from the back of the gypsum board. Gypsum board layer(s) installed over Soundproof Barrier the design.

For L500 series designs, one layer of membrane applied over the subfloor with adhesive and/or nails per manufacturer\'s recommendations. Finish floor attached per manufacturer\'s instructions.

Last Updated on 2006-01-09

Copyright © 2006 Underwriters Laboratories Inc.

The appearance of a company s name or product in this database does not in itself assure that products so identified have been manufactured under ULs Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under ULs Follow-Up Service. Always look for the Mark on the product.

- UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings).
- The statement Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc.
 must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the
 following format: Copyright © 2006 Underwriters Laboratories Inc.

Solutions for living life quietly